

3.5 HARD DRIVE DATA SHEET

Smart. Safe. Secure.
Video-Optimized Storage



SkyHawk™ leverages Seagate's extensive experience in designing drives purpose-built for video applications.



Best-Fit Applications

- Network video recorders (NVR)
- Video DVRs



SKYHAWK
HEALTH



Key Advantages

ImagePerfect™ firmware is designed to ensure seamless video footage capture in 24x7 workloads¹ that record video from 64 HD cameras.

SkyHawk Health Management actively helps protect your video storage by focusing on prevention, intervention, and recovery options.² Included is RAID RapidRebuild™, which provides 3x faster volume rebuilds over traditional RAID rebuilds.

Unparalleled data protection with included 3-year Rescue Data Recovery Services plan, helping protect important video data with Seagate's in-house data recovery services.

RV sensors built in allow drives to maintain performance in multi-bay systems, giving customers the flexibility to scale their systems when more storage is needed.

ATA streaming support enables recordings from up to 64 HD cameras for smooth, uninterrupted footage.

1M hours MTBF, 3-year limited warranty³ represents an improved total cost of ownership (TCO) with reduced maintenance costs.

Lower power consumption means a reduction in heat emissions, which improves reliability in surveillance solutions. Tarnish-resistant components help protect drive from environmental elements, increasing field reliability.

¹ SkyHawk video drives are designed for always-on workloads of 180TB/year. For higher transaction workloads, see Seagate's enterprise-class drive offerings.

² Contact your Seagate sales representative for further information.

³ Seagate does not recommend operating at sustained extreme temperatures. Operating at higher temperatures will reduce useful life of the products.



Specifications	1TB
Standard Model Numbers	ST1000VX005
SkyHawk™ Health Management Included	—
Interface	SATA 6Gb/s
Recording Technology	CMR
Drive Design	Air
Features and Performance	
Drive Bays Supported	Up to 8
Cameras Supported	Up to 64
RV Sensors	—
Max Sustained Transfer Rate OD (MB/s)	180MB/s
Cache (MB)	64
Reliability/Data Integrity	
Tarnish Resistant	Yes
Load/Unload Cycles	—
Nonrecoverable Read Errors Rate, Max	1 per 10E14
Power-On Hours per year	8760
Workload Rate Limit (WRL) ¹	180
Mean Time Between Failures (MTBF) (hours)	1,000,000hr
Warranty, Limited (years) ²	3
Rescue Data Recovery Services (years) ³	—
Power Management	
Startup Current, Typical (12V, A)	1.8
Average Operating Power (W)	5.6W
Idle Average (W)	4.0W
Standby Mode/Sleep Mode, Typical (W)	0.5/0.5
Voltage Tolerance (5V)	±5%
Voltage Tolerance (12V)	±10%
Environmental/Temperature	
Operating (ambient, min °C)	0
Operating (drive reported, max °C) ⁴	70
Nonoperating (ambient, min °C)	-40
Physical	
Height (mm/in, max)	20.20mm/0.795in
Width (mm/in, max)	101.85mm/4.01in
Depth (mm/in, max)	146.99mm/5.787in
Weight (g/lb, typical)	415g/0.915lb
Carton Unit Quantity	25
Cartons per Pallet/Cartons per Layer	40/8

1 SkyHawk surveillance drives are designed for always-on workloads of 180TB/year. For higher transaction workloads, see Seagate's enterprise-class drive offerings.

2 Extended warranty options available. Consult your distributor for details.

3 From May 1, 2020, 3-year Rescue Data Recovery Services plan may be offered in addition to standard warranty. This is offered for selected regions only. Check with reseller on availability.

4 Seagate does not recommend operating at sustained extreme temperatures. Operating at higher temperatures will reduce useful life of the products.